



SPRINKLER STANDARD

Standard Spray Sprinkler

Upright Răspuns rapid / Quick Response

Model / Model : DY3423/DY3433

Răspuns / Response : Rapid/Quick

Clasa de risc / Hazard class : Ușoară și normală/Light and ordinary hazards



Factorul K / K factor : K5,6 (80); K8,0 (115)

Filet / Thread size : 1/2" NPT (15mm); 3/4" NPT (20mm)

Aspect / Finished : Nichelat, alamă neprelucrată/Nickel plated, raw brass

Temperatură / Temperature : Vezi rating / See temperature ratings table

Caracteristici / Characteristics



Răspuns Standard / Standard Response Răspuns Rapid / Quick Response

5 mm

3 mm



Portocaliu/Orange

57 °C



Roșu/Red

68 °C



Galben/Yellow

79 °C



Verde/Green

93 °C



Albastru/Blue

141 °C

No	Denumire / Part Name	Material/ Material
1	Corp / Body	Alamă/ Brass / CW 602N
2	Deflector / Deflector	Oțel inox / Stainless Steel / CF8
3	Bulb / Bulb	Sticlă + lichid / Glass + Liquid
4	Suport bulb / Bulb Seating	Alamă / Brass / CW 602N
5	Etanșare/ Sealing	Aliaj Be-Ni +Teflon / Be-Ni Alloy + Teflon Coated

