



Prestcom
Instal SRL

DY3323/DY3333



SPRINKLER STANDARD

Standard Spray Sprinkler

Upright

Răspuns Standard / Standard Response

Model / Model : DY3323/DY3333

Răspuns / Response : Standard/Standard

Clasa de risc / Hazard class : Ușoară și normală/Light and ordinary hazards



Factorul K / K factor : K5,6 (80); K8,0 (115)

Filet / Thread size : 1/2" NPT (15mm); 3/4" NPT (20mm)

Aspect / Finished : Nichelat, alamă neprelucrată/Nickel plated, raw brass

Temperatură / Temperature : Vezi rating / See temperature ratings table

Caracteristici / Characteristics



Răspuns Standard Răspuns Rapid
Standard Response Quick Response
5 mm 3 mm

		Portocaliu/Orange	57 °C
		Roșu/Red	68 °C
		Galben/Yellow	79 °C
		Verde/Green	93 °C
		Albastru/Blue	141 °C

No	Denumire / Part Name	Material/ Material
1	Corp / Body	Alamă/ Brass / CW 602N
2	Deflector / Deflector	Oțel inox / Stainless Steel / CF8
3	Bulb / Bulb	Sticlă + lichid / Glass + Liquid
4	Suport bulb / Bulb Seating	Alamă / Brass / CW 602N
5	Etanșare/ Sealing	Aliaj Be-Ni + Teflon / Be-Ni Alloy + Teflon Coated
6	Duză / Grub	Oțel inox / Stainless Steel / CF8

