



Prestcom
Instal SRL

DY3329/DY3339



SPRINKLER STANDARD

Standard Spray Sprinkler

Sidewall

Răspuns Standard / Standard Response

Model / Model : DY3329/DY3339

Răspuns / Response : Standard/Standard

Clasa de risc / Hazard class : Toate/All hazards



Factorul K / K factor : K5,6 (80); K8,0 (115)

Filet / Thread size : 1/2" NPT (15mm); 3/4" NPT (20mm)

Aspect / Finished : Nichelat, alamă neprelucrată, vopsit/Nickel plated, raw brass, painted

Temperatură / Temperature : Vezi rating / See temperature ratings table

Caracteristici / Characteristics



Răspuns Standard

Standard Response

5 mm



Răspuns Rapid

Quick Response

3 mm



Portocaliu/Orange

Roșu/Red

Galben/Yellow

Verde/Green

Albastru/Blue

57 °C

68 °C

79 °C

93 °C

141 °C

No	Denumire / Part Name	Material/ Material
1	Corp / Body	Alamă/ Brass / CW 602N
2	Deflector / Deflector	Oțel inox / Stainless Steel / CF8
3	Bulb / Bulb	Sticlă + lichid / Glass + Liquid
4	Suport bulb / Bulb Seating	Alamă / Brass / CW 602N
5	Etanșare/ Sealing	Aliaj Be-Ni + Teflon / Be-Ni Alloy + Teflon Coated
6	Duză / Grub	Oțel inox / Stainless Steel / CF8

